



Decoplast Exterior Top Coat

64 Standard Colors / Custom Colors

TECHNICAL DATA

REPORT TEST METHOD TEST CRITERIA TEST RESULTS

Tensile Strength ASTM D-412 310
psi

Flexibility, Mandrel ASTM D-522 At 70°F (21°C) > 32 (no crack)
Bend % Elongation

Adhesion Concrete ASTM D-4541 420
Psi

Water Vapor Permeability ASTM E-96 ICC Vapor Permeable Pass

Decoplast Exterior Top Coat is 100% acrylic-based interior and exterior wall coating used over prepared concrete, masonry, plaster/stucco and acrylic textured coatings.

Coverage

590-690 ft² (49-58 m²) per pail for a single coat, applied at 12-14 mils (0.3 to 0.36 mm), wet to achieve 8.4 - 10.8 mils DFT per coat.

295-345 ft² (25-29 m²) per pail for two coats, applied at 12-14 mils (0.3 to 0.36 mm) per coat, wet to achieve 8.4 - 10.8 mils DFT per coat.

FEATURES BENEFITS

Pure acrylic Excellent adhesion **Vapor permeable** Allows substrate to breathe naturally **Water-Based** Safe, non-toxic; cleans up with water **UV Resistant** Excellent color retention **Low VOC** Safe for workers and the environment

Packaging

5 gal pail (19L) 52.5 lbs / 23.8 kg per pail

Shelf Life

24 months, if properly sealed and stored.

Storage

Store off the ground in a cool/dry area. Protect from extreme heat [90°F (32°C)], moisture and direct sunlight.

SURFACE PREPARATION

Surfaces must be clean, dry, and free of frost, damage, releasing agents, including dirt, efflorescence, form oil and other foreign matter. Loose or damaged material must be removed by water blasting, sandblasting or mechanical wire brushing and repaired. Avoid application over irregular surfaces. Resurface, patch or level surfaces to required tolerance and smoothness with appropriate Decoplast leveling materials.

Optimum Performance: Roll or spray Deco-Prep bonding agent over substrate prior to application of Decoplast Exterior Top Coat.

Pressure washing is a recommended means of surface preparation. Follow necessary safety precautions and adjust pressure to avoid damage to the underlying substrate or substrate condition. For mold, algae, and mildew removal, treat surfaces with a commercial mildew removal and/or wash product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.



Decoplast Exterior Top Coat

64 Standard Colors / Custom Colors

MIXING

Mix with a clean, rust-free electric drill and paddle to a uniform consistency. Close container when not in use. Clean tools with water immediately after use.

APPLICATION

Apply only to sound and clean, dry, properly prepared surfaces.

Do not apply over damp surfaces or during rain, hail, or snow events or if rain, hail, or snow is imminent. Apply Decoplast Exterior Top Coat in two uniform coats by brush, roller or with proper spray equipment to prepared/primed substrate. Apply coating in a continuous application, always working from a wet edge or architectural break to eliminate cold joints. Back roll open texture surfaces such as concrete masonry. Achieve 8.4 - 10.8 DFT per coat. Allow sufficient time for drying between coats.

Curing/Drying Time

Times assume 70° F (21° C) and 50% relative humidity. Drying time varies with temperature/humidity and surface conditions. Protect installed product from rain, freezing, and continuous high humidity until completely dry.

Clean Up

Clean all tools and equipment immediately with water. Cured material

LIMITATIONS

Use Decoplast Exterior Top Coat only when surface and ambient temperatures are above 40°F (4°C) and below 100°F (38°C) during application and drying period.

Store Decoplast materials in a cool, dry place.

Sloped surfaces: Refer to Decoplast details.

Decoplast Exterior Top Coat should not be used on weather-exposed horizontal or below grade surfaces or where immersion in water may occur.

Do not apply Decoplast Exterior Top Coat to frozen surfaces.

Do not overcoat with solvent-based materials.

HEALTH AND SAFETY

Health Precaution

Decoplast Exterior Top Coat is water-based. As with any chemical construction product, exercise care when handling.

WARNING!

Causes eye and skin irritation.

Safety Precaution

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

First Aid:

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eye lids with fingers. Get immediate medical attention.

SKIN CONTACT: Immediately wash skin with plenty of soap and water for at least 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

INHALATION: If inhaled, remove to fresh air. If not breathing give artificial respiration or give oxygen by trained personnel. Seek medical attention immediately.

INGESTION: If swallowed, do NOT induce vomiting. Call a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.

Spills

Contain and clean with appropriate absorbent materials.

Disposal

Dispose of in accordance with local, state or federal regulations.

Warning

KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. Consult the Safety Data Sheet (SDS) for further health and safety information.

LIMITED WARRANTY

This product is subject to a written

limited warranty. Refer to Decoplast literature for more complete information on the scope and handling of this product.



697 Oakwood Avenue, West Hartford, CT 06110
voice: 860.761.2830 fax: 860.761.2831
www.decoplast.com

This product is intended for use by qualified professional contractors. All information conforms to the standard detail recommendations and specifications for the installation of Decoplast systems. GREENMAKER INDUSTRIES ASSUMES NO LIABILITY, EXPRESSED OR IMPLIED, AS TO THE WORKMANSHIP, ENGINEERING OR ARCHITECTURE OF ANY PROJECT. For more information regarding this product or additional Decoplast products, please contact a Decoplast Representative at (860) 761-2830 or visit our website www.Decoplast.com.