



DecoGlaze

12 Standard Colors

TECHNICAL DATA

REPORT	TEST METHOD	TEST CRITERIA	TEST RESULTS
VOC (g/L)		This product complies with US EPA (40 CFR 59) and South Coast AQMD (Rule 1113) VOC emission standards for architectural coatings. VOC less than 50 g/L.	

Decoplast DecoGlaze is a ready-mixed, acrylic-based exterior or interior decorative wall glaze. It produces beautiful aesthetics with varied degrees of mottling, coloration and glazing. Intended for use as an accent over properly prepared Acrylic Textured Finishes.

FEATURES BENEFITS

Ready-Mixed	Ready to use on site; no additional additives needed
Pure acrylic	Excellent adhesion
Water-Based	Safe, non-toxic; cleans up with water
Vapor permeable	Allows substrate to breathe naturally

Coverage

Coverages may vary depending on application technique and surface conditions and substrate.

SURFACE PREPARATION

All surfaces must be fully cured, structurally sound and free of weak or damaged surface conditions such as laitance or spalls. Surfaces must be clean, dry, frost-free, and free of any bond-inhibiting materials such as dust, dirt, oil, form release, algae, mildew, salts, efflorescence, or any other surface contamination.

Packaging

5 gal pail (19L) 40 lbs / 18 kg per pail

Shelf Life

24 months, if properly sealed and stored.

MIXING

Mix with a clean, rust-free electric drill and paddle to a uniform consistency. Close container when not in use. Clean tools with water immediately after use.

Storage

Store off the ground in a cool/dry area. Protect from extreme heat [90°F (32°C)], moisture and direct sunlight.

APPLICATION

Apply only in well-ventilated areas to structurally sound, clean, dry, properly prepared and primed, frost-free surfaces.

IMPORTANT! Always construct a mock-up under actual conditions of use to verify proper surface preparation, number of coats required, and approval of finished look by the appropriate authority.

DecoGlaze may be applied with a roller, brush, sponge, sprayer, or any combination of these tools depending on the desired end appearance. Once material is applied, it may be dabbed with a sponge or rag to create custom look. It is best to apply DecoGlaze in two light coats as opposed to one heavy coat as this may produce a white haze.

Be sure to watch for running, brush or roller marks, as they should be corrected right away.



DecoGlaze

12 Standard Colors

APPLICATION CONTINUED

Curing/Drying

Decoplast DecoGlaze dries within 24 –72 hours under normal conditions [70°F (21°C), 50% RH]. Drying time varies with temperature, humidity and surface conditions.

Clean Up

Clean tools and equipment with water immediately after use. Remove dried material from tools and equipment mechanically.

LIMITATIONS

Use DecoGlaze only when surface and ambient temperatures are above 40°F (4°C) and below 100°F (38°C) during application and drying period.

Store Decoplast materials in a cool, dry place.

Sloped surfaces: Refer to Decoplast details.

DecoGlaze should not be used on weather-exposed horizontal or below grade surfaces or where immersion in water may occur.

Do not apply DecoGlaze to frozen surfaces.

HEALTH AND SAFETY

Health Precaution

Decoplast DecoGlaze is water-based. As with any chemical construction product, exercise care when handling.

WARNING!

Causes eye and skin irritation.

Safety Precaution

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

First Aid:

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eye lids with fingers. Get immediate medical attention.

SKIN CONTACT: Immediately wash skin with plenty of soap and water for at least 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

INHALATION: If inhaled, remove to fresh air. If not breathing give artificial respiration or give oxygen by trained personnel. Seek medical attention immediately.

INGESTION: If swallowed, do NOT induce vomiting. Call a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.

Spills

Contain and clean with appropriate absorbent materials.

Disposal

Dispose of in accordance with local, state or federal regulations.

Warning

KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. Consult the Safety Data Sheet (SDS) for further health and safety information.

LIMITED WARRANTY

This product is subject to a written limited warranty. Refer to Decoplast Specifications for more complete information on proper use and handling of this product.



697 Oakwood Avenue, West Hartford, CT 06110
voice: 860.761.2830 fax: 860.761.2831
www.decoplast.com

This product is intended for use by qualified professional contractors. All information conforms to the standard detail recommendations and specifications for the installation of Decoplast systems and is presented in good faith as of the date of publication of this document. GREENMAKER INDUSTRIES ASSUMES NO LIABILITY, EXPRESSED OR IMPLIED, AS TO THE WORKMANSHIP, ENGINEERING OR ARCHITECTURE OF ANY PROJECT. For more information regarding this product or additional Decoplast products, please contact a Decoplast Representative at (860) 761-2830 or visit our website www.Decoplast.com.