

Adex Non-Cementitious Adhesive.

SEC. 07240 Submittal Sheet

Description:

- Adex is an adhesive designed to bond EPS foam insulation boards to exterior gypsum board as well as approved un-painted exterior plywood. Adex may be used on alternate substrates, see your Decoplast representative for further information.

Preparation:

- The entire surface should be clean and free of any contaminants.
- Surface and air temperature should be at a minimum of 45°F during and at least 24 hours after the application.

Mixing:

- Using a Goldblatt Jiffy Mixer, or equivalent, mix the finish until uniform consistency is attained.

Application:

- Decoplast Approved Substrate:

Decoplast Adex is applied directly to the back of the EPS foam insulation board. Using a 3/8" stainless steel trowel with a "U" notch apply Adex with even lines. The coated EPS board should be placed on the substrate slightly away from its final position, then slid into position spreading the Adex coating between the EPS and the substrate.

(Fasteners may be used to temporarily hold the EPS boards in place on contoured substrates until the Adex is cured)



"Solutions without compromise"

697 Oakwood Avenue, West Hartford, CT 06110

voice: 860-761-2830 fax: 860.761.2831

www.decoplast.com



Adex Non-Cementitious Adhesive.

SEC. 07240 Submittal Sheet

Physical Properties:

Bond Strength - ASTM C297 56 psi
Flexibility: Will accomodate reasonable movement of wood sheathing due to expansion and contraction without reduction of bond.
Vapor Transmission: Does not create a vapor barrier when installed properly.

Limitations:

- Protect the material from freezing.
- Finishes must be applied at or above 45°F
- Do not apply on damp surfaces or when rain is forecasted.
- Consult the manufacturer's Material Safety Data Sheets.
- Store Decoplast materials in a cool, dry place.
- Protect from freezing and direct sunlight.
- Store at no less than 4°C (40°F)
- Shelf life is 2 years when un-opened and stored as directed.

Cleaning Cautions

- Clean equipment and containers with water immediately after use.
- Protect work from freezing.
- Handle with care.
- Consult the manufacturer's Material Safety Data Sheets.

Availability

- Decoplast Adex is available only at authorized Decoplast Distributors

Coverage

- 300 Square feet per 5 gallon pail.
- Pail weight: 69 lbs.

Disclaimer

Greenmaker Industries will not be held liable for incidental and consequential damages, directly sustained, nor for any loss caused by application of these goods not in accordance with current manufacturers instructions or other than the intended use. Our liability is expressly limited to replacement of defective goods only. Any claim will be considered waived unless made in writing to us within thirty days from the date it was discovered.



697 Oakwood Avenue, West Hartford, CT 06110

voice: 860-761-2830 fax: 860.761.2831

www.decoplast.com